

Lumenwerx 

Flair Cylinder

CYLINDRICAL SOPHISTICATION



3" Flair, Fully Frosted 3/4" Diffuser - Direct/Indirect Pendant
 3" Flair, Partially Frosted 3/4" Diffuser - Direct/Indirect Wall



Flair

Decorative Cylinders

The Flair collection includes three models that enrich spaces with quality illumination and a clean modernist aesthetic. While the Flair Sleeve celebrates the essential geometric form of the cylinder, the Flair Diffuser sports a translucent cover on one or both ends for a tailored, sophisticated finish. The Flair Glow Ring Cylinder gives a slightly more streamlined look with its sleek glow ring detail.



DIAMETERS

- 2" Flair Diffuser
- 3" Flair Diffuser, Sleeve and Glow Ring

HEIGHTS

6", 8", 12" + custom

MOUNTING

Surface,
Pendant, Wall

XPoint™ Refraction
Technology



Left: Flair Diffuser 3" Direct/Indirect Pendant
Center: Aera 3" Downlight Trimless and Arq Flair Pendant
Right: Flair Sleeve 3" Surface and Aera Flex Recessed



Define spaces and accentuate usage with cylinder fixtures and downlights.



Direct Distribution Options



FLAIR SLEEVE

- options:
- Flush sleeve
 - 1/4" sleeve



FLAIR DIFFUSER

- 3 options:
- Fully frosted 1/4" diffuser
 - Fully frosted 3/4" diffuser
 - Partially frosted 3/4" diffuser



FLAIR GLOW RING

- 3/4" Glow Ring





Overview

Flair

SHAPES

○ Round

COLOR RENDERING OPTIONS

80, 90, 95

HEIGHTS


6", 8", 12" + custom

COLOR TEMPERATURES


- 2700K
- 3000K
- 3500K
- 4000K

- Sola
- Duo
- Full
- Spectrum LED

DISTRIBUTIONS



MOUNTING OPTIONS




APERTURE SIZES

2", 3"

TRIM FINISHES

- Textured Matte Black
- Textured Matte White
- Custom RAL

BEAM ANGLES (SLEEVE + GLOW RING)



OPTICAL OPTIONS

Flair Sleeve: Brass, copper, black, white and custom
 Flair Diffuser: Fully frosted and partially frosted
 Flair Glow Ring



Flair Glow Ring
Surface, Champagne Finish

Crown Kitchens
Residential Project,
Brooklyn, New York, U.S.



CYLINDER
BROCHURE



FLAIR CYLINDER
ONLINE

 **Lumenwerx**

ALWAYS LIGHT
RIGHT

lumenwerx.com
R.02.2026