

Lumenwerx 

Ubik Collection

SHINING OUTSIDE
THE BOX





Index



10 UBIK LINEAR



14 UBIK COMBINATION



18 UBIK CUBE



24 UBIK PERIMETER




32 UBIK SEAL PERIMETER



34 UBIK SEAL




36 UBIK TROFFER



44 UBIK SEAL TROFFER

46 UBIK LINEAR APPLICATION GUIDE



Ubik's eye-catching, raised-border end cap adds an elegant finishing touch.



Contour end cap option



Ubik Collection

Shining outside the box


Define, punctuate, and enrich your spaces with Ubik. Install pendant and wall fixtures as individual luminaires or in continuous runs and patterns. Balance lit and unlit areas to create contrast and drama with a chiaroscuro effect.

Up to 1600 lm/ft

Low glare with a UGR of 6*

145 lm/W (HLO)

Optical flexibility with parabolic louvers, HLO, wall wash or blanks



Flat end cap option
*3500K, 500lm, black louvers



Meet the Collection

Versatile and Varied

LINEAR


Play with lines, patterns, and corners.

Define, punctuate, enrich your spaces with Ubik. Install pendant and wall fixtures as individual luminaires or in continuous runs and patterns. Balance lit and unlit areas to create contrast and drama with a chiaroscuro effect. Enabled by our High-Efficiency Lambertian Optic (HLO), Ubik can transform dim corners into bright design features.

Seal Option Available.



Parabolic louvers



HLO






Wall wash

COMBINATION

Variety is the spice of light.

Mix and match optics to add interest and functional diversity to spaces. Parabolic louvers are available in three matte colors—black, silver, and white—HLO, and blanks. Create patterns or combinations, the possibilities are unlimited with Ubik.



Parabolic louvers - HLO - Wall wash - Blanks



CUBE (linear downlight and pendant)

Compact, flexible, and powerful.

Cubes act as linear downlights or pendant option offered with three, six, and nine cells. They are available with parabolic louvers, HLO, and wall wash optics. Performance ranges up to 2400 lumens delivered.



3 cells



6 cells



9 cells

Parabolic louvers - HLO - Wall wash

PERIMETER

Where wall and ceiling meet...

Enjoy perimeter lighting that gently washes down your wall from the edge of the ceiling. Available in leveled, shallow, and deep recessed, Ubik Perimeter can enhance any space with a soft, low-glare ambiance.

Seal Option Available.




Parabolic louvers - HLO

ARCHITECTURAL TROFFER

Sophistication in a square

Add visual comfort and reduce glare with Ubik Troffer, offered with centered parabolic louvers and side lenses that provide indirect, reflected, soft diffused distribution using Tri-flect technology.

Seal Option Available.




2x2



Ubik cube (linear downlight)
6-cell parabolic louver
9-cell wall wash

Ubik pendant
Single unit, parabolic louver



Geometric harmony
in a square.



Optic	Parabolic		
	Matte White	Matte Black	Matte Silver
Finish	Matte White	Matte Black	Matte Silver
Beam angle (FWHM)	91°	89°	86°
UGR*	12	6	8
Efficacy (lm/W)	137	109	125



Ubik Linear

Performance

Ubik is one of the most commanding 2" aperture luminaires on the market, packing a powerful punch of up to 1600 lumens per foot. With five standard lumen packages, Ubik also has the flexibility to illuminate many types of spaces. And if that weren't enough, optics are interchangeable within the same linear run, allowing for even more creative options.

POE AND BIOS TECHNOLOGY

PoE and Bios technology available.



WELL BUILDING

Ubik collection meets the WELL building standard for UGR of <19 in all available lumen packages

WELL

UNITY POINTED (UP) TECHNOLOGY

For our entire Ubik collection, once you decide the output, each luminaire, regardless of shape and size, will emit identical luminous intensity values, precisely measurable down to the square inch with Unity Pointed (UP) technology.

UGR 6

Black parabolic louvers offer an industry best range of 6-8 UGR.

137 lm/W


Ubik is an industry standout with 137 lm/W delivered with parabolic louvers.

L90 < 150 000 hrs

Offering exceptional lifespan with TM-21 certified L90 >60,000 hrs and extrapolated L90 of up to 150,000 hrs.



Low-glare subtle illumination
 Ubik wall mount
 Direct/Indirect option



Ubik Wall Mount

Wall mounting Ubik offers low-glare subtle illumination, ideal for corridors, waiting rooms, stairwells, and more. You can choose direct or direct/indirect and select parabolic louvers or HLO for direct illumination, or WIO and TIO for indirect illumination. Ubik wall luminaires are sophisticated and easy on the eyes.

PARABOLIC LOUVERS



Matte White



Matte Black



Matte Silver

HLO



Ubik Combination

Sleek square form meets superb function in Ubik, a lighting family designed to provide a multitude of creative options. With the Ubik Combination pendant luminaire, you can combine different optics and create patterns with corners to further enhance your lighting design. These compact 2" wide pendant fixtures are offered with HLO, parabolic louvers, and wall wash optics for direct illumination. For indirect, you can select wide-spread or translucent optics.

UP TO
1600 lm/ft

Low glare with
a UGR of 6

145 lm/W
(HLO)

OPTICS
Optical flexibility
with parabolic
louvers, HLO,
wall wash
or blanks



Patterns, Corners and Combinations

With Ubik, designers can turn a single fixture into the focal point of a room or compose patterns within which optics can be combined to enrich visual interest even further.

Ubik Combination

Lit corners

Light corners seamlessly using HLO, which can be combined with wall wash and parabolic louver optics, as well as blanks.

Pendant



Ubik pendants can be used with a leveled corner arrangement.

Recessed

Ubik recessed luminaires offer leveled, inner, and outer corner configuration options.


Wall

Ubik wall fixtures can be installed with leveled inside and outside corners.



Unlit corners

Corners can be unlit when you desire a smooth continuation of the lighting design. Unlit corners can match up to HLO, parabolic louvers, wall wash, or an additional blank unlit section.





Ubik Cube

Linear downlight or pendant

Ubik Cube delivers exceptional performance and versatility. Available in both linear downlight and pendant versions, the compact fixture is offered with HLO, parabolic louver, or wall wash optics. For the parabolic louvers, three matte (MPL) finishes are available in black, silver, and white. Similarly, our wall wash optics are available in black, silver, and white. For pendants, three standard housing colors are available (white, black and aluminum).

PARABOLIC LOUVERS



Matte Black



Matte Silver



Matte White

WALL WASH



Matte Black




Matte Silver



Matte White

HLO








Ubik Cube

Performance

A cube of three cells can serve as the perfect accent, while a longer cube of nine cells can create powerful general illumination or wall washing. Performance ranges up to 2400 lumens delivered.

Performance							Options		
# of cells	Size	Output Integral	lm/W Louvers ¹	lm/W Wall wash ¹	lm/W HLO	Color Temp.	Optics	Mounting	Trim Options for Downlight
03 	6 in	800 lm	137 lm/W	104 lm/W	145 lm/W	2700K 3000K 3500K 4000K Bios Duo ¹ Sola ¹	HLO Parabolic Louvers Wall wash	Recessed Pendant	Trim Trimless Drywall mud flange
06 	12 in	1600 lm							
09 	18 in	2400 lm							

Ubik, Recessed, 3500K, 80 CRI, white louvers finish






Optical Flexibility

Ubik Linear
Ubik Combination,
Ubik Cube

INDIRECT OPTIONS


Wide Indirect Optic

Ubik features the second generation of Wide Indirect Optic (WIO) offering impeccable indirect performance. With 8' spacing, the ideal to 2:1 ratio can be achieved with a 24" drop for best-in-class performance. Fixtures can be placed as close as 12" from the ceiling without creating undesirable hot spots.



Translucent Indirect Optic


Translucent Indirect Optic (TIO) is a simple optic that is ideal for mounting far from the ceiling. It also is very effective with Ubik wall mounted fixtures.



DIRECT OPTIONS


Parabolic Louvers

All parabolic louvers emit soft brightness at the critical viewing angle delivering low-glare environments. They are the ideal solution for task lighting. Distribution can change slightly based on the color of the louvers. All feature a low-glare conical distribution, thereby limiting ceiling brightness.




High-Efficiency Lambertian Optic (HLO)

HLO is a clean, smooth acrylic lens that creates melodic lines of light. Given that the lens is flush rather than recessed, the distribution allows higher angles of light on vertical surfaces. HLO is the perfect optic to create a bright, open space.



Wall Wash

Wall wash is available in pendants, combinations, and cubes, and can achieve uniformity ratios of 3.5:1 on a 10' wall. Ubik wall wash offers a fully lit lens in a 2" square louver.





Brighten and broaden a space
by illuminating perimeter walls.



Ubik Perimeter

Ubik Perimeter offers subtle, low-glare illumination in leveled, shallow, and deep recessed arrangements with parabolic louvers or HLO (High-Efficiency Lambertian Optic). Ubik Perimeter creates uniform illumination on walls, the effects of which can open up an entire space. Use it in offices, showrooms, corridors, hospitality locations, and more.



2.5" aperture
opening

Three mounting
positions

Low-glare
perimeter solution

Option of
parabolic louvers
or HLO




Ubik Perimeter

Performance


Ubik Perimeter with its small aperture (2.5") can yield big and distinct results. Level, shallow, and deep-recessed housing options provide for dramatic, softer, or subtle looks respectively. Use parabolic louvers to add a subtle scalloping architectural effect emphasizing wall texture, or benefit from our HLO (High-Efficiency Lambertian Optic) and its smooth perimeter expression.

UP TO
1200 lm/ft


UP TO
129 lm/W



Parabolic Louver



HLO






Ubik Perimeter

Construction

Ubik Perimeter is designed to offer lines of light that are seamless even at section transitions and corner junctions. The fixture can be mounted in a variety of ceiling systems (gypsum, t-bar, Armstrong TechZone, etc.), and for each option, the driver is positioned to be accessed from below the ceiling.

MOUNTING POSITIONS
















Ubik Perimeter HLO




Ubik Linear

Overview

SIZE	COLOR RENDERING OPTIONS	MOUNTING OPTIONS
2.6" wide	80+ 90+ (R9 > 50)	 Pendant  Recessed  Wall
COLOR TEMPERATURES	DISTRIBUTION	LOUVER FINISHES
<ul style="list-style-type: none">  2700K  3000K  3500K  4000K  Sola 	<ul style="list-style-type: none">  Duo  bios 	<ul style="list-style-type: none">  Direct  Direct / Indirect  Indirect
VARIATIONS	DIRECT OPTICS	INDIRECT OPTICS
<ul style="list-style-type: none"> Linear Continuous runs Patterns Cubes (linear downlight) Combinations Perimeter 	<ul style="list-style-type: none"> Parabolic Louvers High-Efficiency Lambertian Optic Wall Wash 	<ul style="list-style-type: none"> Wide Indirect Optic Translucent Indirect Optic




Ubik has so many options to create fascinating spaces from wall mount to cube to recessed fixtures.





Combine Ubik Seal Perimeter and Ubik Seal to create even illumination in corridors or as a wayfinding solution.

Ubik Seal Perimeter



Ubik Seal Perimeter offers subtle, low-glare illumination in leveled, shallow, and deep recessed arrangements with parabolic louvers. A gasketed clear polycarbonate lens is mounted on top of the louvers for extra protection. Ubik Seal Perimeter can brighten and broaden a space by illuminating perimeter walls. Use it in corridors, nurses' stations, offices, hospitality locations, and more.

UP TO
1200 lm/ft

Low-glare
perimeter solution

Three mounting
positions





Ubik Seal

Ubik Seal is a recessed linear with excellent UGR with three choices of louver color: Matte White, Matte Black, and Matte Silver. An additional gasketed clear polycarbonate lens is mounted on top of louvers for extra protection. Ubik Seal can be installed as a stand-alone luminaire or in a continuous run.



Fully sealed with IP54 rating


UP TO
1200 lm/ft

Low glare with a UGR of 6



reddot winner 2021





Ubik Troffer 2x2



Ubik

Troffer

Ubik's 2x2 troffer brings style, sophistication, and a new dimension to the Ubik linear series, not to mention two color options for center channel louvers.

Size: 2x2

Low glare

Two louver color options

Easy maintenance from below the ceiling






Ubik Troffer

Performance

Ubik Troffer creates visual comfort with its low-glare dual optical chamber performance. The center channel features the parabolic louvers that deliver a soft conical distribution. The side lenses provide indirect, reflected, soft diffused distribution using Tri-flect technology. The fixture offers 60/40 and 40/60 light distribution options and meets the WELL Building Standard™ guidelines for UGR values.




2x2, MPL & TFO,
60/40

UP TO
4500 lm

UP TO
117 lm/W

LOW GLARE
UGR<19





bios WELL™



Ubik Troffer

Overview


SIZE	COLOR RENDERING OPTIONS	MOUNTING OPTIONS
2x2	80+ 90+ (R9 > 50)	T-Bar Drywall
COLOR TEMPERATURES	DISTRIBUTION	LOUVER FINISHES
<ul style="list-style-type: none"> 2700K 3000K 3500K 4000K Sola 	<ul style="list-style-type: none"> Duo bios 	<ul style="list-style-type: none"> Matte White Matte Black Matte Silver
PROFILE		



Sophistication in a Square



Ubik Troffer
2x2, silver parabolic louvers



Optimal visual comfort
with Ubik



Ubik Seal Troffer

Ubik's 2x2 Troffers bring style, sophistication, not to mention two color options for center channel louvers. Our Ubik Seal Troffer has the optional feature of two-circuit control, one for the parabolic louvers in the center channel, the other for the side lenses.





Fully Sealed option (IP54)

Two-circuit control available

Optional IP64 door with polycarbonate lens and tamper-resistant screws

Easy maintenance from below the ceiling



Optimal visual comfort with Ubik Seal Troffer



Ubik Linears Application Guide





General lighting

Ubik is offered in five standard lumen packages to allow for the best interior lighting environments to be created. Whether you choose direct or direct/indirect, Ubik is a comfortable luminaire. If you want ultra-low glare, Ubik black parabolic louvers offer an industry best UGR (between 6 and 8 depending on the output selected). If you want more vertical brightness, then HLO is the solution. You can mix and match in the same linear run with louvers and HLO and also use the Ubik cube downlight to set off the space.

UP TO
1600 lm/ft

Lit or unlit
corners

Linear Patterns
and Combinations

Ubik Cubes (linear
downlights)

Unmatched
Glare Control

UGR as low
as 6 with black
parabolic
louvers



Wall Washing

A unique feature of the Ubik wall wash is that on higher walls of up to 20', the wall wash maintains excellent performance that surpasses that of leading competitors, which essentially stop performing beyond wall heights greater than 10'.

Wall height	10 ft	15 ft	20 ft
Max/min	3.5:1	9.5:1	13.5:1

Ubik, 3500K, wall wash, set back: 30 inch, spacing : 3 ft


Fully lit lens that matches the Ubik direct look

Available in Ubik Linear, Cube and Combination

Recommended Set back: 18"-30"



Amazing uniformity up to **3.5:1** max/min



Ubik: 3500K
Optic: wall wash
Wall height: 20"

Ubik wall wash eclipses the competition on walls as high as **20 ft**



Wide Indirect Optic

This second generation of Wide Indirect Optic offers an impressive beam spread of 140 degrees, and is compatible for high-ceiling application with a far reach in all directions within the 140 degree range.

Spacing (center to center)	8 ft	10 ft	12 ft
Max/min	2:1	4:1	5:1

Ubik, 3500K, 18 ft, pendant, mounting height 24 in

Uniformity of 2:1

Can be mounted 12 inches from the ceiling

Far reaching indirect




2:1 max to min
Uniformity on ceiling




Lumenwerx Solutions

Lumenwerx continues to expand, offering you more lighting solutions with the goal of bringing you the best luminaires in performance, technology, and style for your design needs.





UBIK
BROCHURE



UBIK
ONLINE

 **Lumenwerx**

ALWAYS LIGHT
RIGHT

lumenwerx.com
R.03.2026